

MEDIKA 200 ECT-F TOUCH

Cod. MED0202

Medical Device EMDN V0899

General features



Disclaimer:
Images are purely
indicative. The features
and the accessories of the
products may differ
according to model and
application.

Intended use

Refrigerator destined to store and preserve vaccines, pharmaceutical products, bacterial cultures, samples, analysis materials, chemical products, and other laboratory formulas, to support therapy and/or prevention in clinical centers, hospitals, pharmacies, and laboratories.

Temperature range

Adjustable +2°C / +15 °C

Factory setpoint | Increment

+5°C | 0.1°C

Ambient working class | Climatic class

From +16°C to +38°C | N-ST

Nominal capacity

200 lt (7 cu ft)

Gross capacity | Net capacity

221 lt (7,8 cu ft) | 221 lt (7,8 cu ft)

External dimensions (WxDxH)

60x66x146 cm

Internal dimensions (WxDxH)

50x48,5x90 cm

Net weight without any internal fittings

86 kg

Package dimensions | Weight

Cardboard on pallet 65x72x162 cm | weight 96,5 kg
Wooden crate on pallet 72x77x162 cm | weight 106,5 kg

Structure

Monocoque type body, made of plasticized, non-toxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Rounded corners and tray-type inner bottom.

Insulation type

High density (43 kg/m³) in-walls injected PUF, without any CFC, environmental-friendly, water-foam based.

Insulation thickness

70 mm rear / 50 mm sides

Feet

No.4 unidirectional rollers + No.2 stabilizing feet

Door

No.1 door made of tempered and low emissivity glass, self-closing thanks to the spring hinge and 90°stop position.

Lightning

Full LED, all length of inner chamber, automatic switching on at door opening or from the display when the door is closed.

Energy saving functions

Night & Day function

Internal fittings

Customizable and height adjustable, it can mix independently:

- wire shelves supported by adjustable clips (dim.cm 46x45)
- fully extractible drawers made of aluminium, with dividers (WxDxH): cm 11,8x40x7,5 (nr 3 compartments)
- fully extractible drawers made of aluminium, without dividers (WxDxH): cm 39x40x7,5
- st. steel wire drawers on telescopic slides (WxDxH): cm 43,5x40,5x6,2
- st. steel wire shelves supported by adjustable clips (dim.cm.46x45)

Suggested internal fittings

No. 3 wire shelves

Refrigeration system

Refrigeration

Professional, ventilated, forced, hermetic compressor type

Defrost

Automatic, adaptive, including condensate water vaporization

Refrigerant

Natural R290

GWP | ODP

3 | 0

Electronic controller



| | |
|--|--|
| Controller | TOUCH controller |
| Type of controller | Electronic controller, FULL TOUCH SCREEN 7" display, resolution 0,1°C, easily readable from the distance, with a real time temperature graph and all operational data always available on the homepage. |
| Power switch | Integrated in user's interface |
| Security features | Settable user password Visual and acoustic for temperature alarms failures such as: <ul style="list-style-type: none"> • Open door • High temperature • Low temperature • Power failure, signaled when power is back. • Clogged condenser • Any functional failure/faulty parts |
| Alarm system | Latest 32 events displayed, 10 years data recorded on SD card and 1 year on flash memory, downloadable from USB port |
| Data and event recording | |
| Settable temperature limits alarms | Yes |
| Control sensors | NTC type probes for controller board + PT100 for DMLP monitor board (optional) |
| Safety thermostat | Included, to prevent freezing and overheating |
| Connectivity for remote alarms transmission | Set-up on the electronic controller board, can be remoted on request. Modbus TCP/IP protocol available for data reading |
| Temperature recording | Full recording of temperatures and alarms data |
| Data export | USB, SD and RJ45. |

Electrical and functional data

| | |
|---|-----------------------------|
| Standard power supply | 230V / 1ph / 50Hz |
| Standard plug type | Schuko type "G" |
| Compressor protection | Overload Protector included |
| Power absorption/current | kW 0,17 (Amp 1) |
| Inrush current | Amp 3 |
| Noise level | <45 dBA |
| Heat emission according to EN 12900 | W 25 |
| Hold over time at 20°C ambient (air) | 2,1 h (from +5C to +15°C) |
| Energy consumption at 20°C ambient | 0,6 kWh/24h |

Compliance

| | |
|-----------------------------------|---|
| Directives and regulations | The offered unit complies with Regulation (EU) 2017/745 and subsequent modifications and integrations, Risk Class I (All. VIII, Cap. III, Reg. 2). The equipment is also fully compliant with the specific requirements of the norms: Directive 2006/42/EC (Machines Directive), Directive 2014/30/EU (EMC), Directive 2014/35/EU (LVD), Regulation (EU) 2024/573 (F-gas), Directive 2012/19/EU (RAEE) Regulation (EC) n.1907/2006 (REACH) Directive 2011/65/UE (ROHS II) including subsequent modifications and integrations |
| Available certificate | CE |
| Application environment | Non-flammable, non-explosive, non-corrosive, with adequate air exchange |

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 – Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

| | |
|---|---|
| Visual and acoustic alarm for power failure | No.8 rechargeable batteries, AA, Ni-MH type, environmental friendly and easily replaceable, to feed power failure alarm |
| External contacts (Ethernet+ potential free) terminal board | |
| Electric-digital lock with password protection | Digital lock, the door is opened by touching an icon on the display. The function may be password protected. Mechanical release key supplied for emergency opening. |
| GSM module (including buffer batteries) | Plug-in module to notify on mobile phones, via sms, overall monitoring, alarms and failures of the refrigerator |
| Converter module type 4-20mA (including contacts terminal board) | External contacts included (this accessory excludes the installation of the GSM module) |
| Wi-Fi module | Plug-in module to connect to, monitor and manage the refrigerator wirelessly |
| Compliance kit to DIN 13277 | Includes the electric digital lock, buffer batteries for power failure alarm signal and the external terminal board with potential free contact |
| DMLP TOUCH Digital Monitor | Visual, acoustic alarm and fully independent recording system, with accuracy 0,1 °C thanks to the PT100 probes used for temperature detection. DMLP will take over alarming function when installed as integrated module on the Ect-f Touch controller board. The module is fed by standard rechargeable batteries (power failure alarm batteries included) to register temperatures and events even in case of power outage. Data download and their management are made possible by CAPTURE software, supplied on board on the SD card, through which tables and graphs are created |
| PT100 product temperature simulation probe | |
| FIOCCHETTI COLD EYES cloud monitoring | Annual monitoring service, Cloud based, featuring the notification of alarms and failures from pc thanks to a dedicated app, including SMS messages and emails, also allowing the full download of recorded data. |
| FIOCCHETTI LAN SUPERVISOR | Monitoring system allowing the supervision of one or several refrigerators thanks to the access to historical data and to present equipment status. It allows the creation and export of temperature graphs of selected periods or of specific hours. A single license enables the connection of up to 100 refrigerators installed in the same building and connected to the same net (e.g., a hospital). |
| Solid type door | Please refer to LABOR series |
| Additional wire shelf kit | |
| Extractible drawer on telescopic slides | |
| Extractible drawer without inner dividers on telescopic slides | |
| St. steel wire shelf kit | |
| St. steel wire drawer on telescopic slides | |
| Lockable drawer for narcotics H mm 100 | |
| Rack 140x420x150H mm (max 3 per each shelf) | |
| Plexiglas front panel for extractible drawer | |
| Castors kit with brakes | |
| Internal Socket (no.1) | |
| 35 mm access port with stopper | |
| Port hole mm 15 | |
| Humidity sensor | |
| PT100 sensor with free contacts | |
| Mains voltage stabilizer | |
| Non-standard plug and cable | |
| Power 220V/60Hz | |
| Power 115V/60Hz | |
| Wooden crate package | |

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028
www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it