

General features



Temperature range	Adjustable +2°C / +15 °C
Factory setpoint Increment	+5°C 0.1°C
Ambient working class Climatic class	From +16°C to +38°C N-ST

Nominal capacity	700 lt (24,7 cu ft)
Gross capacity Net capacity	668 lt (23,6 cu ft) 668 lt (23,6 cu ft)
External dimensions (W X D x H)	75 x 90,5 x 210 cm
Internal dimensions (W x D x H)	60 x 74 x 150 cm
Net weight without any internal fittings	175 kg

Package dimensions Weight	Cardboard on pallet 77 x 90 x 214 cm weight 161 kg Wooden crate on pallet 84 x 94 x 214 weight 174 kg
------------------------------------	--



Structure	Monocoque type body, made of plasticized, atoxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Inner bottom rounded corners.
------------------	--

Insulation type	High density (43 kg/m ³) in-walls injected PUF, without any CFC, environmental-friendly, water-foam based.
------------------------	--

Insulation thickness	75 mm
-----------------------------	-------

Feet	No.4 adjustable feet
-------------	----------------------

Door	No.2 doors made of tempered glass, triple thickness, self-closing thanks to the spring hinge and 90°stop position.
-------------	--

Lightning	Full LED, all length of inner chamber, automatic switching on at door opening or from the display when the door is closed.
------------------	--

Internal fittings	Customizable and height adjustable, it can mix independently: <ul style="list-style-type: none"> • wire shelves supported by adjustable clips (dim.cm 56x66) • st. steel wire shelves supported by adjustable clips (dim.cm.56x66) • rack mm 140x500x150H (Max. 3 per shelf)
--------------------------	---

Suggested internal fittings	No. 3 wire shelves
------------------------------------	--------------------

Refrigeration system

Refrigeration	Professional, ventilated, forced, hermetic compressor type
Defrost	Automatic, adaptive, including condensate water vaporisation
Refrigerant	Natural R290
GWP ODP	3 0

Disclaimer:
Images are purely indicative. The features and the accessories of the products may differ according to model and application..

Electronic controller



Controller	Controller ECT-F control®
Type of controller	Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C
Power switch	Integrated in user's interface
Security features	Settable user password
Alarm system	Visual and acoustic for temperature alarms and failures such as: <ul style="list-style-type: none">• Open door• High temperature• High temperature caused by power failure.• Low temperature• Power failure (when the energy returns, only in event of High Temperature)• Clogged condenser• Any functional failure/faulty parts
Data and event recordings	Last 12 events available on the display
Settable temperature alarm limits	Yes, through parameter adjustment

Control sensors	NTC type probes
------------------------	-----------------

Electrical and functional data

Standard power supply	230V / 1ph / 50Hz
Standard plug type	Schuko type "G"
Compressor protection	Overload Protector included
Power absorption/current	kW 0,12 (Amp 0,7)
Inrush current	Amp 2,5
Noise level	<55 dBA
Heat emission according to EN 12900	W 125
Hold over time at 20°C ambient (air)	2,3 h (from +5°C to +15°C)
Energy consumption at 20°C ambient	3 kWh/24h

Conformity

Directives and regulations	Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH
Available certificate	CE
Application environment	Non-flammable, non-explosive, non-corrosive, with adequate air exchange

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Lock with key

ECT-F PLUS controller

Evolution of ECT-F control® controller, including following additional features:

- Backup batteries for power failure alarm, up to 48 Hrs
- Min and Max temperature log, manually resettable
- High temperature alarm during power failure
- Refrigerator temperature visible even during power failure
- Alarm contact available on control board, remotable
- Additional programmable relays output available

Please refer to model MEDIKA 700 PT ECT-F PLUS

Solid type door

Additional wire shelf kit

St. steel wire shelf kit

Rack 140x420x150H mm (max 3 per each shelf)

Castors kit with brakes

Internal Socket (no.1)

35 mm access port with stopper

Port hole mm 15

Humidity sensor

PT100 sensor with free contacts

Mains voltage stabilizer

Non-standard plug and cable

Power 220V/60Hz

Power 115V/60Hz

Wooden crate package

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it