

General features



Disclaimer:
Images are purely
indicative. The features
and the accessories of the
products may differ
according to model and
application.

Temperature range	Adjustable +2°C / +15 °C
Factory setpoint Increment	+5°C 0,1°C
Ambient working class Climatic class	From +16°C to +38°C N-ST
Nominal capacity	700 lt (24,7 cu ft)
Gross capacity Net capacity	668 lt (23,6 cu ft) 668 lt (23,6 cu ft)
External dimensions (WxDxH)	75x90,5x210 cm
Internal dimensions (WxDxH)	60x74x150 cm
Net weight without any internal fittings	175 kg
Package dimensions Weight	Cardboard on pallet 77x90x214 cm weight 161 kg Wooden crate on pallet 84x94x214 weight 174 kg
Structure	Monocoque type body, made of plasticized, atoxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Inner bottom rounded corners.
Insulation type	High density (43 kg/m ³) in-walls injected PUF, without any CFC, environmental-friendly, water-foam based.
Insulation thickness	75 mm
Feet	No.4 adjustable feet
Door	No.2 doors made of tempered glass, triple thickness, self-closing thanks to the spring hinge and 90°stop position.
Lightning	Full LED, all length of inner chamber, automatic switching on at door opening or from the display when the door is closed.
Internal fittings	Customizable and height adjustable, it can mix independently: wire shelves supported by adjustable clips (dim.cm 56x66) st. steel wire shelves supported by adjustable clips (dim.cm.56x66) rack mm 140x500x150H (Max. 3 per shelf)
Suggested internal fittings	No. 3 wire shelves

Refrigeration system

Refrigeration	Professional, ventilated, forced, hermetic compressor type
Defrost	Automatic, adaptive, including condensate water vaporisation
Refrigerant	Natural R290
GWP ODP	3 0

Electronic controller



Controller	ECT-F PLUS controller
Type of controller	Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C
Power switch	Integrated in user's interface
Security features	Settable user password Visual and acoustic for temperature alarms and failures such as: Open door High temperature High temperature caused by power failure.
Alarm system	Low temperature Power failure (alarm back up up to 48h) Clogged condenser Faulty batteries Any functional failure/faulty parts
Data and event recordings	Last 12 events available on the display
Settable temperature alarm limits	Yes, through parameter adjustment
Control sensors	NTC type probes
Connection for remote alarm signalisation	Ready on the board, remote on request
Temperature recording	Log of minimum and maximum temperature reached, manual reset
Data export	Not available

Electrical and functional data

Standard power supply	230V / 1ph / 50Hz
Standard plug type	Schuko type "G"
Compressor protection	Overload Protector included
Power absorption/current	kW 0,12 (Amp 0,7)
Inrush current	Amp 2,5
Noise level	<55 dBA
Heat emission according to EN 12900	W 125
Hold over time at 20°C ambient (air)	2,3 h (from +5°C to +15°C)
Energy consumption at 20°C ambient	3 kWh/24h

Conformity

Directives and regulations	Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH
Available certificate	CE
Application environment	Non-flammable, non-explosive, non-corrosive, with adequate air exchange

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Lock with key	
External dry contact	
Anty-freeze safety	
DIN 13277 conformity (includes anty-freeze safety)	Includes: anti-freezer safety, key lock, buffer batteries for power failure alarm and external terminal board with dry contact
Temperature chart recorder	
Solid type door	
Additional wire shelf kit	
St. steel wire shelf kit	
Rack 140x500x150H mm (max 3 per each shelf)	
Castors kit with brakes	
Internal Socket (no.1)	
35 mm access port with stopper	
Port hole mm 15	
Humidity sensor	
PT100 sensor with free contacts	
Mains voltage stabilizer	
Non-standard plug and cable	
Power 220V/60Hz	
Power 115V/60Hz	
Wooden crate package	

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it