

General features



| | |
|--|----------------------------|
| Temperature range | Adjustable +2°C / +15 °C |
| Factory setpoint Increment | +5°C 0.1°C |
| Ambient working class Climatic class | From +16°C to +38°C N-ST |

| | |
|---|--|
| Nominal capacity | 100 lt (3,53 cu ft) |
| Gross capacity Net capacity | 126 lt (4,45 cu ft) 96 lt (3,40 cu ft) |
| External dimensions (W X D x H) | 52 x 63,5 x 71 cm |
| Internal dimensions (W x D x H) | 44 x 51,6 x 42,1 cm |
| Net weight without any internal fittings | 46 kg |



| | |
|------------------------------------|--|
| Package dimensions Weight | Cardboard on pallet 55 x 69 x 87 cm weight 55 kg Wooden crate on pallet 60 x 77 x 103 cm weight 64,5 kg |
|------------------------------------|--|

| | |
|------------------|--|
| Structure | Monocoque type, made of plasticized, non-toxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Rounded corners and tray-type inner bottom, |
|------------------|--|

| | |
|------------------------|---|
| Insulation type | High-density (43 kg/m ³), in-walls injected PUF, without any CFC, water-foam based. |
|------------------------|---|

| | |
|-----------------------------|-------|
| Insulation thickness | 40 mm |
|-----------------------------|-------|

| | |
|-------------|----------------------------|
| Feet | No.4 adjustable small feet |
|-------------|----------------------------|

| | |
|-------------|---|
| Door | No.1 solid door with ergonomic handle, self-closing thanks to the spring hinge and 90° stop position. |
|-------------|---|

| | |
|------------------|--|
| Lightning | Full LED, all length of inner chamber, automatic switching on at door opening. |
|------------------|--|

| | |
|--------------------------|--|
| Internal fittings | Customizable and height adjustable, it can mix independently: <ul style="list-style-type: none"> • wire shelves supported by adjustable clips (dim.cm.40x49) • fully extractible drawers made of aluminium, with dividers (WxDxH): cm 10x45x7,5 (nr 3 compartments) • fully extractible drawers made of aluminium, without dividers (WxDxH): cm 33x45x7,5 |
|--------------------------|--|

| | |
|------------------------------------|------------------|
| Suggested internal fittings | No. 1 wire shelf |
|------------------------------------|------------------|

Refrigeration system

| | |
|----------------------|--|
| Refrigeration | Professional, ventilated, forced, hermetic compressor type |
| Defrost | Automatic, adaptive, including condensate water vaporisation |
| Refrigerant | Natural R290 |
| GWP ODP | 3 0 |

Disclaimer:
Images are purely
indicative. The
features and the
accessories of the
products may differ
according to model
and application.

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Electronic controller



| | |
|--|--|
| Controller | Controller ECT-F control® |
| Type of controller | Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C |
| Power switch | Integrated in user's interface |
| Security features | Settable user password |
| Alarm system | Visual and acoustic for temperature alarms and failures such as: <ul style="list-style-type: none">• Open door• High temperature• High temperature caused by power failure.• Low temperature• Power failure (when the energy returns, only in event of High Temperature)• Clogged condenser• Any functional failure/faulty parts |
| Data and event recordings | Last 12 events available on the display |
| Settable temperature alarm limits | Yes, through parameter adjustment |

| | |
|------------------------|-----------------|
| Control sensors | NTC type probes |
|------------------------|-----------------|

Electrical and functional data

| | |
|---|-----------------------------|
| Standard power supply | 230V / 1ph / 50Hz |
| Standard plug type | Schuko type "G" |
| Compressor protection | Overload Protector included |
| Power absorption/current | kW 0,14 (Amp 0,9) |
| Inrush current | Amp 2,5 |
| Noise level | <40 dBA |
| Heat emission according to EN 12900 | W 20 |
| Hold over time at 20°C ambient (air) | 3,8 h (from +5°C to +15°C) |
| Energy consumption at 20°C ambient | 0,5 kWh/24h |

Conformity

| | |
|-----------------------------------|---|
| Directives and regulations | Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH |
| Available certificate | CE |
| Application environment | Non-flammable, non-explosive, non-corrosive, with adequate air exchange |

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Lock with key

DMLP Digital Monitor®

Alarm and temperature recording system completely independent from the ECT-F control® controller, equipped with buffer battery and featuring an additional backlit, alphanumerical LCD display.

DMLP Digital Monitor provides:

- Temperature and alarms data recording on extractible SD card covering the last 5 years, with one minute sampling frequency.
- Back-up buffer battery granting alarms and recording during power cut. The life of the battery is approximately 12 hours during power failures.
- Pre-set for alarms remoting (dry contact)

The SD can be inserted in any pc using a card-reader and includes a freely supplied software, Capture, allowing to download, save and print any data.

Information can be arranged as a graph or tabular forms, both fully customizable.

DMLP Printer

ECT-F PLUS controller

Evolution of ECT-F control® controller, including following additional features:

- Backup batteries for power failure alarm, up to 48 Hrs
- Min and Max temperature log, manually resettable
- High temperature alarm during power failure
- Refrigerator temperature visible even during power failure
- Alarm contact available on control board, remotable
- Additional programmable relays output available

Please refer to model LABOR 100 ECT-F PLUS

Additional wire shelf kit

Extractible drawer on telescopic slides

Extractible drawer without inner dividers on telescopic slides

Plexiglas front panel for extractible drawer

Castors kit with brakes

One-way small castors

Inner socket (no.1)

35mm access port with stopper (no.1)

Port hole mm 15 (no.1)

No.1 humidity sensor

No.1 PT100 sensor with free contacts

Non-standard plug and cable

Power 220V/60Hz

Power 115V/60Hz

Mains voltage stabilizer

Wooden crate package

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it