



Disclaimer:  
Images are purely  
indicative. The features  
and the accessories of the  
products may differ  
according to model and  
application.

### General features

<b>Temperature range</b>	Chamber A adjustable between +2°C / +15°C Chamber B adjustable between -10°C / -20°C
<b>Factory setpoint   Increment</b>	+5°C   0.1°C chamber A -20°C   0.1°C chamber B
<b>Ambient working class   Climatic class</b>	From +10°C to +25°C   C
<b>Nominal capacity</b>	350 + 350 lt (12,36 + 12,36 cu ft)
<b>Gross capacity   Net capacity</b>	288 + 305 lt (10,17 + 10,77 cu ft)   260+265 lt (9,19 + 9,37 cu ft)
<b>External dimensions (WxDxH)</b>	72x85,5x203 cm
<b>Internal dimensions (WxDxH)</b>	60x68x70 / 60x68x74 cm
<b>Net weight without any internal fittings</b>	159 kg
<b>Package dimensions   Weight</b>	Cardboard on pallet 76x92x212 cm   weight 174 kg Wooden crate on pallet 84x98x212 cm   weight 187 kg
<b>Structure</b>	Monocoque type, made of plasticized, non-toxic white steel interior, coated with a special antibacterial-type film; exterior in 18/10 AISI 304 stainless steel. Rounded corners and tray-type inner bottom, High-density (43 kg/m <sup>3</sup> ), in-walls injected PUF, without any CFC, water-foam based.
<b>Insulation type</b>	
<b>Insulation thickness</b>	60 mm
<b>Feet</b>	No.4 adjustable feet
<b>Door</b>	No.2 doors made of tempered glass, triple thickness, self-closing thanks to the spring hinge and 90°stop position.
<b>Lightning</b>	Full LED, all length of inner chamber, automatic switching on at door opening or from the display when the door is closed.
<b>Internal fittings</b>	Customizable and height adjustable, it can mix independently: wire shelves supported by adjustable clips (dim.cm 56x65) fully extractible drawers made of aluminium, with dividers (WxDxH): cm 15x60x7,5 (nr 3 compartments) fully extractible drawers made of aluminium, without dividers (WxDxH): cm 49x60x7,5 st. steel wire basket on telescopic slides (WxDxH): cm 53,8x63x14,8 st. steel wire drawers on telescopic slides (WxDxH): cm 53,8x60,5x6,2 st. steel wire shelves supported by adjustable clips (dim.cm.56x66)
<b>Suggested internal fittings</b>	No. 4 wire shelves (2 + 2)

### Refrigeration system

<b>Refrigeration</b>	Professional, ventilated, forced, hermetic compressor type. No. 2 separate and independent cooling systems, one for each compartment.
<b>Defrost</b>	Automatic, adaptive, with collection of condensate water
<b>Refrigerant</b>	Natural R290
<b>GWP   ODP</b>	3   0

#### FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy

VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

[www.fiocchetti.com](http://www.fiocchetti.com) - Email: [info@fiocchetti.it](mailto:info@fiocchetti.it) - Pec: [fiocchetti@pec.it](mailto:fiocchetti@pec.it)

## Electronic controller



<b>Controller</b>	ECT-F PLUS controller
<b>Type of controller</b>	Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C
<b>Power switch</b>	Integrated in user's interface
<b>Security features</b>	Settable user password Visual and acoustic for temperature alarms and failures such as: Open door High temperature High temperature caused by power failure.
<b>Alarm system</b>	Low temperature Power failure (alarm back up up to 48h) Clogged condenser Faulty batteries Any functional failure/faulty parts
<b>Data and event recordings</b>	Last 12 events available on the display
<b>Settable temperature alarm limits</b>	Yes, through parameter adjustment
<b>Control sensors</b>	NTC type probes
<b>Connection for remote alarm signalisation</b>	Ready on the board, remote on request
<b>Temperature recording</b>	Log of minimum and maximum temperature reached, manual reset
<b>Data export</b>	Not available

## Electrical and functional data

<b>Standard power supply</b>	230V / 1ph / 50Hz
<b>Standard plug type</b>	Schuko type "G"
<b>Compressor protection</b>	Overload Protector included
<b>Power absorption/current</b>	kW 0,17 + 0,32 (Amp 1 + 2,3)
<b>Inrush current</b>	Amp 3 + 5
<b>Noise level</b>	<50 dBA
<b>Heat emission according to EN 12900</b>	W 291
<b>Hold over time at 20°C ambient (air)</b>	5 h chamber A (from +5°C to +15°C) 2,5 h chamber B (from -20°C to 0°C)
<b>Energy consumption at 20°C ambient</b>	7 kWh/24h

## Conformity

<b>Directives and regulations</b>	Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH
<b>Available certificate</b>	CE
<b>Application environment</b>	Non-flammable, non-explosive, non-corrosive, with adequate air exchange

### FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy

VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

[www.fiocchetti.com](http://www.fiocchetti.com) - Email: [info@fiocchetti.it](mailto:info@fiocchetti.it) - Pec: [fiocchetti@pec.it](mailto:fiocchetti@pec.it)

## Accessories available on request

Lock with key (only for upper part)	
External dry contact	
Anty-freeze safety	
DIN 13277 conformity (includes anty-freeze safety)	Includes: anti-freezer safety, key lock, buffer batteries for power failure alarm and external terminal board with dry contact
Additional wire shelf kit	
Extractible drawer on telescopic slides	
Extractible drawer without inner dividers on telescopic slides	
St. steel wire shelf kit	
St. steel wire drawer on telescopic slides	
St. steel wire basket on telescopic slides	
Perforated stainless steel shelf	
Lockable drawer for narcotics H mm 100	
Rack 140x500x150H mm (max 3 per each shelf)	
Plexiglas front panel for extractible drawer	
Castors kit with brakes	
Inner socket (no.1)	
35mm access port with stopper (no.1)	
Port hole mm 15 (no.1)	
Tray for automatic evaporation of condensate water	
No.1 humidity sensor	
No.1 PT100 sensor with free contacts	
Non-standard plug and cable	
Power 220V/60Hz	
Power 115V/60Hz	
Mains voltage stabilizer	
Wooden crate package	

### FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy  
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028  
[www.fiocchetti.com](http://www.fiocchetti.com) - Email: [info@fiocchetti.it](mailto:info@fiocchetti.it) - Pec: [fiocchetti@pec.it](mailto:fiocchetti@pec.it)