

Caratteristiche generali



Disclaimer:
Images are purely
indicative. The features
and the accessories of the
products may differ
according to model and
application.

Temperature range	Adjustable +2°C / +15°C for both compartments
Factory setpoint Increment	+5°C 0.1°C for both compartments
Ambient working class Climatic class	From +16°C to +38°C N-ST
Nominal capacity	500 + 500 lt (17,6 + 17,6 cu ft)
Gross capacity Net capacity	527 + 527 lt (18,6 + 18,6 cu ft) 527 + 527 lt (18,6 + 18,6 cu ft)
External dimensions (WxDxH)	144 (72 + 72)x76x208 cm
Internal dimensions (WxDxH)	60x58x150 cm (x2)
Net weight without any internal fittings	266 kg
Package dimensions Weight	No. 2 cardboards on pallet 76x81x220 cm each weight 147 kg each No. 2 wooden crates on pallet 84x85x220 cm weight 159 kg each
Structure	No. 2 monocoque type body, made of plasticized, non-toxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Rounded corners and tray-type inner bottom.
Insulation type	High density (43 kg/m ³) in-walls injected PUF, without any CFC, environmental-friendly, water-foam based.
Insulation thickness	75 mm rear / 60 mm sides
Feet	No. 4 unidirectional rollers + No. 2 stabilizing feet
Door	No. 2 doors made of tempered and low emissivity glass, self-closing thanks to the spring hinge and 90°stop position.
Lightning	Full LED, all length of inner chamber, automatic switching on at door opening or from the display when the door is closed.
Internal fittings	Customizable and height adjustable, it can mix independently: • wire shelves supported by adjustable clips (dim.cm 55x56) • fully extractable drawers made of aluminium, with dividers (WxDxH): cm 15x50x7,5 (nr 3 compartments) • fully extractable drawers made of aluminium, without dividers (WxDxH): cm 49x50x7,5
Suggested internal fittings	No. 8 wire shelves (4 + 4)

Refrigeration system

Refrigeration	Professional, ventilated, forced, hermetic compressor type. No. 2 separate and independent cooling systems, one for each compartment.
Defrost	Automatic, adaptive, including condensate water vaporisation
Refrigerant	Natural R290
GWP ODP	3 0

Electronic controller



Controller	Controller ECT-F control®
Type of controller	Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C
Power switch	Integrated in user's interface
Security features	Settable user password Visual and acoustic for temperature alarms and failures such as: • Open door • High temperature • High temperature caused by power failure. • Low temperature • Power failure (when the energy returns, only in event of High Temperature) • Clogged condenser • Any functional failure/faulty parts
Alarm system	
Data and event recordings	Last 12 events available on the display
Settable temperature alarm limits	Yes, through parameter adjustment
Control sensors	NTC type probes

Electrical and functional data

Standard power supply	230V / 1ph / 50Hz
Standard plug type	Schuko type "C"
Compressor protection	Overload Protector included
Power absorption/current	kW 0,17 + 0,17 (Amp 1 + 1)
Inrush current	Amp 3 + 3
Noise level	<45 + 45dBA
Heat emission according to EN 12900	W 41 + 41
Hold over time at 20°C ambient (air)	3,5 h (da +5°C a +15°C)
Energy consumption at 20°C ambient	1 + 1 kWh/24h

Conformity

Directives and regulations	Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH
Available certificate	CE
Application environment	Non-flammable, non-explosive, non-corrosive, with adequate air exchange

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Lock with key	
ECT-F PLUS controller	Evolution of ECT-F control® controller, including following additional features: • Backup batteries for power failure alarm, up to 48 Hrs • Min and Max temperature log, manually resettable • High temperature alarm during power failure • Refrigerator temperature visible even during power failure • Alarm contact available on control board, remotable • Additional programmable relays output available Please refer to model MEDIKA 2T 1000 ECT-F PLUS
Solid type door	Please refer to LABOR series
Additional wire shelf kit	
Extractible drawer on telescopic slides	
Extractible drawer without inner dividers on telescopic slides	
Lockable drawer for narcotics	
Rack 140x420x150H mm (max 3 per each shelf)	
Plexiglas front panel for extractible drawer	
Castors kit with brakes	
Internal Socket (no.1)	
35 mm access port with stopper	
Port hole mm 15	
Humidity sensor	
PT100 sensor with free contacts	
Mains voltage stabilizer	
Non-standard plug and cable	
Power 220V/60Hz	
Power 115V/60Hz	
Wooden crate package	

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

www.fiocchetti.com - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it