

General features



| | |
|--|----------------------------|
| Temperature range | Adjustable +2°C / +15 °C |
| Factory setpoint Increment | +5°C 0.1°C |
| Ambient working class Climatic class | From +16°C to +38°C N-ST |

| | |
|---|---|
| Nominal capacity | 700 lt (24,7 cu ft) |
| Gross capacity Net capacity | 620 lt (21,9 cu ft) 620 lt (21,9 cu ft) |
| External dimensions (W x D x H) | 75 x 82,5 x 210 cm |
| Internal dimensions (W x D x H) | 60 x 68,5 x 150 cm |
| Net weight without any internal fittings | 128 kg |

| | |
|------------------------------------|---|
| Package dimensions Weight | Cardboard on pallet 77 x 90 x 214 cm weight 145 kg Wooden crate on pallet 84 x 94 x 214 cm weight 158 kg |
|------------------------------------|---|



| | |
|-----------------------------|---|
| Structure | Monocoque type body, made of plasticized, non-toxic white steel interior/exterior, coated with a special antibacterial-type film, or in inner 18/10 Aisi 304 stainless steel. Rounded corners and tray-type inner bottom. |
| Insulation type | High density (43 kg/m ³) in-walls injected PUF, without any CFC, environmental-friendly, water-foam based. |
| Insulation thickness | 75 mm |
| Feet | No.4 adjustable feet |
| Door | No.1 solid door with ergonomic handle all door length, self-closing thanks to the spring hinge and 90° stop position. |



| | |
|------------------------------------|--|
| Internal fittings | Customizable and height adjustable, it can mix independently: <ul style="list-style-type: none"> • wire shelves supported by adjustable clips (dim.cm 56x65) • fully extractible drawers made of aluminium, with dividers (WxDxH): cm 15x60x7,5 (nr 3 compartments) • fully extractible drawers made of aluminium, without dividers(WxDxH): cm 49x60x7,5 • st. steel wire basket on telescopic slides (WxDxH): cm 53,8x63x14,8 • st. steel wire drawers on telescopic slides (WxDxH): cm 53,8x60,5x6,2 • st. steel wire shelves supported by adjustable clips (dim.cm.56x66) |
| Suggested internal fittings | No. 3 wire shelves |

| | |
|--------------------------------------|--------------------------------------|
| Additional construction notes | Without internal electrical contacts |
|--------------------------------------|--------------------------------------|

Refrigeration system

| | |
|----------------------|--|
| Refrigeration | Professional, ventilated, forced, hermetic compressor type |
| Defrost | Automatic, adaptive, including condensate water vaporisation |
| Refrigerant | Natural R290 |
| GWP ODP | 3 0 |

Disclaimer:
Images are purely indicative. The features and the accessories of the products may differ according to model and application.

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Electronic controller



| | |
|--|--|
| Controller | Controller ECT-F control® |
| Type of controller | Electronic controller, back-lit alphanumeric LCD display and resolution 0,1°C |
| Power switch | Integrated in user's interface |
| Security features | Settable user password |
| Alarm system | Visual and acoustic for temperature alarms and failures such as: <ul style="list-style-type: none">• Open door• High temperature• High temperature caused by power failure.• Low temperature• Power failure (when the energy returns, only in event of High Temperature)• Clogged condenser• Any functional failure/faulty parts |
| Data and event recordings | Last 12 events available on the display |
| Settable temperature alarm limits | Yes, through parameter adjustment |

| | |
|------------------------|-----------------|
| Control sensors | NTC type probes |
|------------------------|-----------------|

Electrical and functional data

| | |
|---|-----------------------------|
| Standard power supply | 230V / 1ph / 50Hz |
| Standard plug type | Schuko type "G" |
| Compressor protection | Overload Protector included |
| Power absorption/current | kW 0,12 (Amp 0,7) |
| Inrush current | Amp 2,5 |
| Noise level | <50 dBA |
| Heat emission according to EN 12900 | W 40 |
| Hold over time at 20°C ambient (air) | 8,8 h (from +5C to +15°C) |
| Energy consumption at 20°C ambient | 1 kWh/24h |

Conformity

| | |
|-----------------------------------|---|
| Directives and regulations | Directive 2006/42/EC (Machine directive) Directive 2011/65/EC (ROHS II) Directive 2015/863/ EC (ROHS III) Directive 2012/19/EC (RAEE) Directive 2014/30/EC (EMC) Directive 2014/35/EC (LVD) Regulation (EU) 517-2014 (F-gas) Regulation (EU) 1907-2006_REACH |
| Available certificate | CE |
| Application environment | Non-flammable, non-explosive, non-corrosive, with adequate air exchange |

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it

Accessories available on request

Lock with key

Controllore ECT-F PLUS

Evolution of ECT-F control® controller, including following additional features:

- Backup batteries for power failure alarm, up to 48 Hrs
- Min and Max temperature log, manually resettable
- High temperature alarm during power failure
- Refrigerator temperature visible even during power failure
- Alarm contact available on control board, remotable
- Additional programmable relays output available

Please refer to model LABOR 700 ECT-F PLUS

Additional wire shelf kit

Extractible drawer on telescopic slides

Extractible drawer without inner dividers on telescopic slides

St. steel wire shelf kit

St. steel wire drawer on telescopic slides

St. steel wire basket on telescopic slides

Perforated stainless steel shelf

Lockable drawer for narcotics H mm 100

Rack 140x500x150H mm (max 3 per each shelf)

Plexiglas front panel for extractible drawer

Castors kit with brakes

35 mm access port with stopper

Port hole mm 15

Humidity sensor

PT100 sensor with free contacts

Mains voltage stabilizer

Non-standard plug and cable

Power 220V/60Hz

Power 115V/60Hz

Wooden crate package

FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

<http://www.fiocchetti.com> - Email: info@fiocchetti.it - Pec: fiocchetti@pec.it