

### MORTUARY CHAMBER 12 BODIES - 4 DOORS

Cod. CAM031204

#### Characteristics



Disclaimer:  
Images are purely  
indicative. The features  
and the accessories of the  
products may differ  
according to model and  
application.

<b>Temperature range</b>	+2 / +8 °C <i>Also available -10 / -20 °C</i>
<b>Capacity</b>	12 bodies on 3 levels
<b>External Dimensions (WxDxH)</b>	cm 374x235x256 External dimensions without monoblock unit: cm 374x235x208
<b>Structure and Insulation</b>	White coated steel inside and outside; insulation polyurethane thickness 80 mm <i>Also available INOX inside and outside.</i>
<b>Door</b>	N. 4 doors (dim. cm 72x150)
<b>Key Lock</b>	
<b>Light</b>	
<b>Internal equipment</b>	N. 12 steel body trays
<b>Controller</b>	Digital electronic thermostat
<b>Alarms</b>	Acoustic and Visual for temperature deviations and failures
<b>Refrigeration Type</b>	Ventilated
<b>Defrost</b>	Automatic with automatic evaporation of the condensate water

#### Technical data

<b>Details</b>	<ul style="list-style-type: none"> <li>Refrigerant type: R290, CFC free</li> <li>Mains Voltage: 230V/1/50Hz</li> <li>Power consumption: kW 0,765 (model -20 °C kW 1,23)</li> <li>Ambient Temperature: +10/+32 °C; humidity 60%</li> </ul>
<b>In accordance with</b>	2006/42/CE, 2014/30/CE, 2014/35/CE and following modifications
<b>Package</b>	Chamber to be installed on site, packed in cellophane on pallet, monoblock in strong cardboard on wooden pallet
<b>Note</b>	Also available in low temperature version (-10 / -20 °C)

### DMLP UNIT

External module with DMLP DIGITAL MONITOR:

Monitor/alarm/recording system with rechargeable battery

- Temperatures and alarms recorder on removable Secure Digital (SD Back-Up memory): it can store 5 years data, recording temperature and alarms every minute.
  - The SD card can be connected to any PC: a software (Capture) is included, so that you can download, save and print all data from your PC
  - Battery backup: ensures alarms and recording of temperatures even in case of power failure. The battery system lasts about 12 hours.
  - Dry contact for remote connection + RS485 port
- 

### DMLP PRINTER

Voltage 220V/1/60Hz

---

Additional body tray

---

Hydraulic trolley H cm 31 - 177

---

Hydraulic trolley with electrical adjustment H cm 38,5 - 201,5

---

Wooden crate Package

---

---

### FIOCCHETTI SCIENTIFIC S.R.L.

Headquarter: Via Panagulis, 48 - 42045 Luzzara (RE) Italy  
VAT No. IT00934960352

Phone +39 0522 976232 - Fax +39 0522 976028

[www.fiocchetti.com](http://www.fiocchetti.com) - Email: [info@fiocchetti.it](mailto:info@fiocchetti.it) - Pec: [fiocchetti@pec.it](mailto:fiocchetti@pec.it)